



FNCINE		
	ENGINE	
Model	Cummins Engine ISGe5-460	
Horsepower	460HP	
Displacement	11.8L	
Max Torque	2300N·m	
Emissions	Euro V	
TRANSMISSION		
Model	HW23712C (Q)	
Type	Mechanic Transmission	
Gears	12 Forward shift+2 Reverse shift	
Clutch	Ф430	
FRO	ONT AXLE	
Model	9000kg	
Brake	Drum Brake	
REAR AXLE		
Model	16000kg	
Brake	Drum Brake	
Speed Ratio	4.76/5.26/5.92	
BRAKE SYSTEM		
Service Brake	Dual-circuit Air Braking System	
Parking Brake	Spring-loaded Air-release Parking Brake	
Auxiliary Brake	Engine Braking Assist	
FUEL TANK		
Tank Size	450L	
Tank Construction	Aluminium alloy	
C	HASSIS	
Thickness	865-225/320×90×(8+7)	
	12.00R20 18PR	
Tire Size	with 1 spare tire	
	CABIN	
Туре	Flat cabin(1 sleepers)	
Driver Seat	Air driver's seat	
A/C	Automated air conditioner	
Cab Reversal	Manual cab reversal	
Windows Lifter	Electrical windows lifter	
MID	IENSIONS	
Length×Width×Height(mm)	9300×2558×3813(mm)	
Wheelbase(mm)	1800+3300+1400mm	
SUS	SPENSION	
Fifth WHEEL	/	
Suspension	Leaf suspension	
'	VEIGHT	
GCW(kg)	80000	
_	DY SPECIFICATION	
Body Internal Dimimension	6300×2350×1600(mm)	
Hydraulic System	Front lifting, HYVA	
Tipping Body Plate Thickness	Bottom 10 mm, Side 8 mm	
Material	T700 High-strength steel	
riatellal	1700 High Strength Steel	

	2. 16	
	المحرك	
ISGe5-460 ک ومینز	الموديل	
460	القدرة الحصانية	
11.8	حجم المحرك باللتر (الإزاحة)	
2300	أقصى عزم دوران (دورة بالدقيقة)	
يورو 5	الانبعاث	
الجيربوكس (ناقل الحركة)		
HW23712C (Q)	الموديل	
ناقل حركة ميكانيكي 12MT	النوع	
أمامي 12 و خلفي2	السر عات	
Ф430	الكانش	
المحور الأمامي		
كغ9000	الموديل	
اسطواني	الفرامل	
ي	المحور الخلف	
كخ16000	الموديل	
اسطواني	الفر امل	
4.76/5.26/5.92	نسبة السرعة	
نظام المكابح		
ثنائي الاسطوانة بمساعدة الهواء	فرامل الخدمة	
فرامل مزودة بنابض بمساعدة الهواء	فرامل الانتظار	
فرامل المحرك	الفر امل المساعدة	
خزان الوقود		
450	سعة الخزان باللتر	
ألمنيوم	مادة الخزان	
	الشاص	
865-225/320×90× (8+7)	الأبعاد	
12.00R20 18PR	الإطارات	
with 1 spare tire	· ·	
الكبين (الغمارة)		
كبين عادي بسرير واحد	النوع	
مقعد مزود بنظام الهواء	مقعد السائق	
أوتوماتيكي	المكيف (تبريد الكبين)	
مانوال - يدوي	فتح و إغلاق الكبين	
كهربائي	زجاج النافذة	
	الأبعاد	
9300×2558×3813	طول - عرض - ارتفاع بالـ مم	
1800+3300+1400	قاعدة المحاور (البعد بين المحورين) بالـ مم	
	نظام التعليق	
/	الرحى	
سست (ریش معدنیة)	التعليق	
الوزن		
80000	الوزن الكلي بالـ كغ	
مواصفات صندوق القلاب		
6300×2350×1600	أبعاد الصندوق الداخلية بالـ مم	
أمامي (هيفا)	نظام الهيدروليك	
الأرضية 10 مم, الجوانب 8 مم	سماكة حديد الصندوق بالـ مم	
صلب عالي الجودة T700	نوع الحديد	

Consult your local authorized dealer for details

Dealer Information:





*Data may differ from this information